



## VP-4 4 Port Video Encoder

### The Ultimate in Enterprise Class IP Video Recording

#### Overview

- 4 channel
- All channels D1 resolution, H.264 at 30FPS
- Dual Stream
- 4 video loop-outs
- Encoder-based motion detection
- De-interlaced images
- PTZ support
- 1 channel Audio in and out
- 4 Digital Inputs and 1 Output



#### Technical Specifications

<b>Video/Audio Input</b>	Video Compression:	Standard H.264
	Video Input:	4-ch, BNC (1.0V p-p, 75Ω)
	Audio Compression:	OggVorbis
	Audio Input:	4-ch, BNC (1.0V p-p, 1 kΩ)
	Audio Input Interface:	BNC(2Vp-p, 1kΩ)
	Voice Talk Input:	1-ch, 3.5mm audio interface (2.0V p-p, 1 kΩ)
<b>Video/Audio Output</b>	Audio Output:	1-ch, 3.5mm audio interface (2.0V p-p, 1 kΩ)
	Encoding Resolution:	QCIF / CIF / 2CIF / 4CIF
	Frame Rate:	25 fps (P) / 30 fps (N)
	Video Bit Rate:	32 kbps ~ 2048 kbps, or user-defined (Max. 3 Mbps)
	Audio Bit Rate:	64 kbps
	Dual Stream:	Supported
	Stream Type:	Video / Video & Audio
<b>External Interface</b>	Network Interface:	1 RJ-45 10M / 100 Mbps self-adaptive UTP Ethernet interface
	Serial Interface:	1 RS-485 interface (PTZ control), 1 RS-232 interface
	Alarm In:	4
	Alarm Out:	2
<b>General</b>	Power Supply:	12 VDC power supply
	Consumption:	≤ 8W
	Working Temperature:	14°F ~ +131°F
	Working Humidity:	10% ~ 90%
	Dimensions (WxDxH):	7.89 x 5.35 x 1.65 in.
	Weight (without HDD):	≤ 4.41 lbs